

Product datasheet

uvex 1 G2 6839 1-4

Safety boot DIN EN ISO 20345:2022 S3L FO SC SR

Sizes: 35 - 52 | Width: 10, 11, 12, 14



AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

TPU outsole uvex x-tended grip planet with 10% recycled granulate from residues



- shock-absorbing and energy-returning uvex i-PUREnrj planet midsole with 15% recycled granulate from residues
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES

Upper material	• breathable microvelour (clima zone) • water-repellent (WPA) • suitable for people allergic to chrome
Lining material	• textile distance mesh lining for comfortable foot climate
Fastening	• laces
Heel basket	• foamed heel basket out of PU for additional stability in the shoe
Comfort	• soft padding on collar • sizes 35-40 have been produced using a women's last • dust tongue
Insock	• removable comfortable insock
Furthermore	• metal-free

PROTECTIVE FEATURES

Toe cap	• metal-free protective toe cap
Penetration resistance	• metal-free, textile penetration resistance
Scuffcap	• out of TPU for additional protection of the upper material (SC)

CERTIFICATES

uvex medicare+	• certified for orthopaedic insocks and shoe adjustments according to the description in DGUV 112-191
100% vegan	• certified free from animal ingredients and products • additional protection for people with allergies and intolerances
ESD	• protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1

SUSTAINABILITY

Recycled/sustainable materials	• outsole, midsole and removable insock made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list
--------------------------------	--

ACCESORIES/ SPARE PARTS

Replacement insock	• 9490 7-0
tune-up insock	• low 95287 • medium 95288 • high 95289
Laces	• black 9599923